

QUANTUM

QUANTUM-1s-XC3



The QUANTUM-1s-XC3 is an IP 3 MegaPixel Box Camera suitable for installation inside weatherproof housings or internally on brackets.

This camera utilises H.265 compression which reduces bandwidth and HDD storage by up to 50% when used in conjunction with one of our H.265 recorders or any VMS which supports H.265.

Its advanced chipset supports intelligent functions such as Heat Mapping, People Counting and many others to provide valuable business intelligence to many industries including the FMCG industry.

The QUANTUM-1s-XC3 also has Ultra WDR (140dB), 2 alarm inputs, 1 alarm output, built in microphone, 1 audio output, Micro SD slot and an Analogue BNC output.



CONNECTIVITY

Ethernet	1 RJ45 (10/100Base-T)
BNC Output (CVBS)	1
Alarm Input	2
Alarm Output	1
Audio Input	1 (Built-in Microphone)
Audio Output	1
RS-485	0
Memory Slot	Micro SD (Max 128GB)

LENS

Focal Length	C/CS Mount
--------------	------------

DAY / NIGHT

Min. Illumination	Colour B/W	0.01Lux @ F1.2 0.001Lux @ F1.2
Day/Night IR Distance	Auto (ICR) / Colour / B&W	n/a

SOFTWARE

Network Functions	IPv4/IPv6, HTTP, HTTPS, SSL, IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Smart Phone/Tablet PC / Mac Software Onvif	ICRSS Pro / ICView Smart ICRSS / Web Browser Onvif, PSIA
Intelligent Functions	Tripwire, Intrusion Detection, Scene Change, Missing / Abandoned Object, Audio Detection, People Counting and Heat Map
Trigger Mode	Manual / Auto (alarm triggered)
Trigger Event	Recording, Email, Snapshot, Relay

ACCESSORIES (OPTIONAL)

IC-BRKT-100	Camera Bracket
IC-L2712-3MP	3MP 2.7-12mm Lens
IC-L550-3MP	3MP 5-50mm Lens

PERFORMANCE

Image Sensor Chipset	Sony Exmor (1/2.8") Ambarella
Effective Pixels	2048(H) x 1536(V)
Compression	H.265/H.264/MJPEG
Resolution	3MP (1-25fps)
Streams	3
Bit Rate	40Kbps-10Mbps
Backlight Compensation	BLC / HLC
Wide Dynamic Range	Ultra WDR (140dB)
White Balance	Auto/Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Other Features	Defog, Electronic Image Stabilisation & Region of Interest

ENVIRONMENTAL

Power Consumption	12vDC / PoE (802.3af) 10W (Max with ICR & ABF)
Working Environment Protection	-30°C - 60°C / Less than 95% RH
Dimensions	71.4 x 65.5 x 135.4mm
Weight	0.58kg



European Head Office
IC Realtime,
12 Knockmitten Lane,
Western Industrial Estate,
Dublin 12,
Ireland

UK Office
IC Realtime UK
Surrey Technology Centre,
40 Occam Road,
Guildford GU2 7YG,
United Kingdom

USA Head Office
IC Realtime, LLC,
3050 N Andrews Ave EXT,
Pompano Beach,
FL 33064,
USA

USA West Coast Office
IC Realtime West Coast,
14180 W Van Buren Street,
Suite B-105, Goodyear,
AZ 85338,
USA